



- **Definer 220**  
Primary Flow Meter



**Bios**  
Driving a Higher Standard  
in Flow Measurement<sup>SM</sup>



**Bios meets the highest quality assurance standards for gas flow measurement uncertainty, including industry-leading ISO 17025, ANSI Z-540 and NIST 150 laboratory accreditation by the National Voluntary Laboratory Accreditation Program (NVLAP) administered by the National Institute of Standards and Technology (NIST).**

## **Bios Definer 220**

The Definer 220 is everything you value about Bios DryCal® Technology in a hand-held flow meter that makes it easier than ever to verify gas flow rates.

**Turn the Definer 220 on. Connect it to your flow stream. Take measurements. It's that simple.**

Whether you're in the field or in the lab, the Definer 220's Quick Start operation will have you up and running in an instant, verifying gas flow rates on the spot. Featuring a number of quality and performance enhancements over traditional flow meter technologies, the Definer 220 offers primary measurement – manually, or in your choice of two hands-free continuous modes – as well as a graphical LCD display, user-selectable flow units and time intervals between measurements. Fully customizable, the Definer 220 gives you exactly what you need, in the format you prefer.

### **Flexible Ways of Working**

No matter your application, the portable Definer 220 is ready to go to work for you. Because it's a true volumetric standard based on the principle of positive displacement, the Definer 220 provides immediate indication of the actual gas flow rate, accurately and independently of the gas type. It also includes integrated temperature sensors and pressure transducers in the flow stream, so you can compensate for standard conditions – allowing traceable verifications of mass flow devices, before or after you use them and wherever they're located.

A versatile, push-button flow meter, the Definer 220 is also a primary flow standard, enabling you to accurately calibrate a variety of instrumentation while maintaining an ISO 17025-traceable audit trail.

### **Optimizer Software**

Take the calibration process one step further and document your results with Definer 220's Optimizer Collect light (included). Bios Optimizer Collect light captures flow data from your Definer 220 directly to a Microsoft Excel® preconfigured spreadsheet. You can upgrade to Bios Optimizer Collect for more features such as hot key commands, instrument library, have multiple instruments interface simultaneously and much more.



## Definer 220

### Primary Flow Meter

With Proven DryCal® Technology.  
Engineered for the process measurement community.






#### Customizing Your Calibrations

The Definer 220's many customizable options are simple and intuitive. Take measurements one at a time, or automate the process using the hands-free Continuous or Burst modes. In all modes, the averaging function is user-selectable from 1 to 100 measurements. Time profile your gas flows with measurement intervals spanning from 1 to 60 minutes. Or, decide how to view your data – use the handy Zoom feature to display the size and detail that's right for you, and select your preferred measurement units.

<b>Flow Ranges</b>	<b>Low (L)</b> 5 scc/min– 500 scc/min* <b>Medium (M)</b> 50 scc/min – 5,000 scc/min* <b>High (H)</b> 300 scc/min – 30,000 scc/min*
<b>Accuracy</b>	1% Standardized / 0.75% Volumetric
<b>Size</b>	Small enough to fit easily in your hand; slim enough to slide into a briefcase or tote
<b>Weight</b>	29 oz / 820 g
<b>Dimensions (H x W x D)</b>	5.5 x 6 x 3 in / 140 x 150 x 75 mm

\*At gas pressure of 760 mmHg, and a gas temperature of 25° centigrade with standardization temperature set to 0° centigrade.

User-Selectable Measurement Units	
<b>Volumetric Flow</b>	mL/min L/min cc/min cf/min
<b>Standard Flow</b>	smL/min sL/min scc/min scf/min
<b>Pressure</b>	mmHg PSI kPa
<b>Temperature</b>	°C °F

-  **Reliable**  
15 years of Proven DryCal® Technology
-  **Accurate**  
Backed by ISO 17025; NVLAP accredited
-  **Portable**  
Lightweight and impact-resistant
-  **Simple**  
Push button testing; no user interpretation or external calculations required
-  **Streamlined**  
Bios Optimizer software transfers calibration data directly to any Windows-based PC using built-in serial port

Definer 220 Specifications	
Approximate Time per Reading:	1-15 seconds
Gas Compatibility:	Use with non-corrosive, non-condensing, non-combustible gases, less than 70% humidity
Flow Modes:	Pressure or Suction
Measurement Cell Style:	Integrated
Temperature and Pressure Sensors:	In the flow stream Press.: 3.5 mmHg (typical), 7.0 mm (max); Temp.: 0.8° C (typical), 1.3° C (max)
Reading Styles:	Single (manual, Continuous or Burst, with averaging function user-selectable from 1 to 100 measurements
AC Adapter/Charger:	12V DC, >250ma, 2.5 mm, center positive
Battery System:	6V rechargeable, sealed lead-acid, 6-8 hrs typical operation
Battery Operational Time (5 cycles/min):	3 hrs backlight on, 8 hrs backlight off
Pressure and Suction Fittings:	¼" ID Swagelok® compression fittings, 3/8" fittings on High Model
Warranty:	1 year; battery 6 months
Storage Temperature:	0-70° C
Ambient Humidity:	0-70%, non-condensing
Operating Pressure (Absolute):	15 PSI
Display:	Backlit graphical LCD
Data Port (for use with Optimizer software):	Serial (RS-232)
Data Cable (for use with Optimizer software):	1 meter (Definer Data Port to PC serial port)
Protective Case:	Soft side or Pelican case available
<b>RoHS- and CE-compliant</b>	

Backed by ISO 17025 and Proven DryCal® Technology, the Definer 220 helps assure compliance with environmental regulations and improves your process control.



The Bios facility in Butler, N.J., (pictured above) is one of the world's most accurate ISO 17025 laboratories serving the environmental and process control industries. With the lowest gas flow measurement uncertainties of any commercial laboratory, Bios provides you with the legal protections and peace of mind valued in today's litigious business environment.



## Bios

**Bios International Corporation**  
10 Park Place  
Butler, NJ, USA 07405

Phone: 973.492.8400  
Toll Free: 800.663.4977  
Fax: 973.492.8270

www.biosint.com  
www.drycal.com